



ATF DEX VI
DEXRON® VI Formula

FEATURES & BENEFITS

Meets or exceeds the following requirements:

- Superior friction retention and consistent smooth shifting
- Advanced additives protect against rust, corrosion and foam
- Enhanced oxidative stability for longer fluid life and extended service interval
- Excellent extreme pressure and anti-wear performance and protection
- Enhanced oxidative stability for longer fluid life and extended service interval
- Wide range of seal compatibility for better leakage prevention



PUREZONE DEX VI is an advanced ATF fluid approved for use in passenger car and light truck automatic transmissions that require a General Motors DEXRON® VI or earlier generation DEXRON® fluid. It is particularly recommended for use in GM 6-speed automatic transmissions and is fully compatible with older GM transmissions and other transmissions calling for Ford MERCON®, Allison C-4, Toyota T-III and T-IV, Honda Z1, Nissan Matic D and Matic J, and Mitsubishi SP-II and SP-III, JASO 1A as well as performance requirements for other Asian OEM's like Hyundai, Subaru and Mazda. In addition it meets the requirements of European OEM's like ZF TE-ML-14A, Voith 55.6335, MAN 339 Type Z-1 and MB, VW and BMW 4- and 5-speed automatic transmission specifications.

TYPICAL RESULTS

Testing Parameters	ATF DEX VI
COLOUR	RED
DENSITY @ 15°C (ASTM D4052) kg/L	0.860
VISCOSITY (D-445)cSt @ 40°C	36.0
VISCOSITY (D-445)cSt @ 100°C	7.0
VISCOSITY INDEX (D-2270)	179
POUR POINT (°C / °F) (D-97)	-51°C / -59.8°F
FLASH POINT (°C / °F) (D-92)	220°C / 428°F

ORDER CODES

ATF DEX VI	
946ml /1 US Qt	ATFVI946M
4.73L /1.25 US Gal	ATFVI473M
18.9L /5 US Gal	ATFVI189M
208L /55 US Gal	ATFVI208M

*FOR MORE PART NUMBERS GO TO PAGE 19