



**ATF MV
MULTI-VEHICLE**

FEATURES & BENEFITS

Meets or exceeds the following requirements:

- Voith extended drain
- ZF (TE-ML.14.B)
- Allison C-4
- Caterpillar TO-2
- ATF +4, ATF +3 capable
- Suitable for use where Dexron® IIIH, IIIG, IIE, or II is recommended
- Maximum value service life in heavy duty fleets provides up to 100,000 miles or 50,000 miles in severe duty conditions as recommended by OEM's



PUREZONE ATF MV is a premium multi-vehicle transmission fluid designed to provide unparalleled severe duty operating performance. This formula was designed to meet the performance requirements of global transmissions from North American, European and Asian transmission manufacturers. Using one fluid for multiple applications reduces the chance for misapplication and reduces the need for multiple products to be carried in inventory.

PUREZONE ATF MV offers excellent fluidity at low temperatures allowing for better lubrication and faster start-times in extremely cold temperatures.

PUREZONE ATF MV protects better and longer than previous automatic transmission fluids to reduce wear and extend the durability of the transmission.

PUREZONE ATF MV is suitable for use in transmissions used in Ford, GM, Chrysler, Toyota, Nissan, Volkswagen, Audi, BMW, Hyundai, Subaru, and Mercedes-Benz vehicles. It can also be used in transmissions where Dexron® III-H, III-G, & II are required.

PUREZONE ATF MV is suitable where Dexron® VI is required.

TYPICAL RESULTS

Testing Parameters	ATF MV
COLOUR	RED
DENSITY @ 15°C (ASTM D4052) kg/L	0.854
VISCOSITY (D-445)cSt @ 40°C	33.0
VISCOSITY (D-445)cSt @ 100°C	7.4
VISCOSITY INDEX (D-2270)	198
POUR POINT (°C / °F) (D-97)	-48°C / - 54.4°F
FLASH POINT (°C / °F) (D-92)	210°C /410.4°F

ORDER CODES

ATF MV	
946ml /1 US Qt	ATFMV946M
4.73L /1.25 US Gal	ATFMV473M
18.9L /5 US Gal	ATFMV189M
22.7L /6 US Gal	ATFMV227M
208L /55 US Gal	ATFMV208M

*FOR MORE PART NUMBERS GO TO PAGE 19