



3 SEASON TRACTOR HYDRAULIC FLUID

FEATURES & BENEFITS

Meets or exceeds the following requirements:

- Lubricates and protects transmissions, differential and final drive gears in tractors and implements
- Excellent extreme pressure and anti-wear performance and protection
- Controlled frictional characteristics enables wet brakes to hold correctly
- Reduces brake chatter and provides smooth engagement of power take-off (PTO) clutches
- Provides excellent results for foam suppression and water sensitivity



PUREZONE TRACTOR Hydraulic Fluid is a premium quality multi-functional tractor hydraulic fluid blended from highly refined base oils and an additive package suitable for use in equipment requiring extended service under severe conditions. It provides excellent oxidation, anti-foam, anti-rust, anti-wear, extreme pressure (EP) protection. It is recommended for final drive, transmission, differential power take-off (PTO) units and wet brake systems.

PUREZONE TRACTOR Hydraulic Fluid has been field-tested and is suitable for use in Allis Chalmers, Allison, Ford Tractor, Caterpillar, International Harvester, Kubota, Deutz, Oliver, White, J.I. Case, Massey Ferguson, John Deere and other manufacturers' equipment where a premium tractor hydraulic fluid is recommended.

TYPICAL RESULTS

| Testing Parameters | 3 SEASON |
|----------------------------------|---------------|
| DENSITY @ 15°C (ASTM D4052) kg/L | 0.8821 |
| VISCOSITY (D-445)cSt @ 40°C | 53 |
| VISCOSITY (D-445)cSt @ 100°C | 9.2 |
| VISCOSITY INDEX (D-2270) | 135 |
| POUR POINT (°C / °F) (D-97) | -29°C / -20°F |
| FLASH POINT (°C / °F) (D-92) | 204°C / 400°F |

ORDER CODES

| 3 SEASON TRACTOR FLUID | |
|--------------------------------------|---------|
| 18.9L / 5 US Gal | TDH189M |
| 208L / 55 US Gal | TDH208M |
| *FOR MORE PART NUMBERS GO TO PAGE 19 | |