

Safety Data Sheet

SECTION 1: PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME:	PUREZONE PCMO Synthetic blend Oil SNGF-5 Includes Grades 5W-20, 5W-30, 10W-30, 10W-40, 15W-40, 20W-50, 3	SDS ID: 82545 30.
SVNONVMS.	Petroleum oil; Lube oil; Petroleum hydrocarbon; Lubricant.	
SYNONYMS: PRODUCT CODE:	Prefix 21	
PRODUCT USE:	For lubricating passenger car motors. If these products are used in combination with other products, refe Safety Data Sheet for those products.	r to the Material

This number is for emergency use only. If you desire non-emergency product information, please call a phone number listed below.

Emergency # 1-778-995-5370

SUPPLIER: Motosel Industrial Group Inc 407-204 Cayer St Coquitlam, BC V3K 5B1 Canada

> 1-888-668-6463 www.motosel.com

Issue Date March 29, 2015 Supersedes Issue Date October 5, 2012 Original Issue Date October 31, 1988

PREPARED BY: Product MSDS Coordinator

APPROVED BY: MSDS Task Force

SECTION 2: HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

APPEARANCE

Liquid, amber, petroleum odor.

CAUTION!

HEALTH HAZARDS

May irritate the respiratory tract (nose, throat, and lungs), eyes, and skin. May be harmful if swallowed.

OSHA Regulated Chemicals

No information is available.

POTENTIAL HEALTH EFFECTS

FOILMIAL MEALINE LITEOIS			
INHALATION (BREATHING):	These products are not likely to present an inhalation hazard at normal temperatures and pressures. However, when aerosolizing, misting, or heating these products, high concentrations of generated vapor or mist may irritate the respiratory tract (nose, throat, and lungs).		
EYES:	May cause irritation.		
SKIN:	May cause irritation. Not likely to be absorbed through the skin in harmful amounts.		
INGESTION (SWALLOWING):	May be harmful if swallowed. May cause throat irritation, nausea, vomiting, and diarrhea.		
MEDICAL CONDITIC AGGRAVATED BY E			
CHRONIC:	Prolonged or repeated inhalation of oil mist may cause oil pneumonia, lung tissue inflammation, and/or fibrous tissue formation. Prolonged or repeated eye contact may cause inflammation of the membrane lining the eyelids and covering the eyeball (conjunctivitis). Prolonged or repeated skin contact may cause drying, cracking, redness, itching, and/or swelling (dermatitis).		
CANCER INFORMATION:	No known carcinogenicity. For more information, see SECTION 11: CARCINOGENICITY.		
	Also see SECTION 15: CALIFORNIA.		

POTENTIAL ENVIRONMENTAL EFFECTS

Not available. Also see SECTION 12: ECOLOGICAL INFORMATION.

	SECTION 3: COMPOSITION/IN	FORMATION ON INGREDIEN	<u>TS</u>
AS # 64742-58-1	Component	Synonym Hydrotreated paraffinic base oil	Wt. Percent 50-92*
	hydrotreated spent		
72623-87-1	Lubricating oils, petroleum, C20-50,	Not Available	0-60*
64742-54-7	hydrotreated neutral oil-based Petroleum distillates, hydrotreated	Not Available	4-42*
72623-86-0	heavy paraffinic Lubricating oils, petroleum, C15-30,	Not Available	0-30*
72623-83-7	hydrotreated neutral oil-based Lubricating oils (petroleum), C>25,	Bright Stock	0-30*
64742-62-7	hydrotreated bright stock Residual oils (petroleum), solvent	Bright Stock	0-30*
64742-57-0	dewaxed Residual oils (petroleum),	Bright Stock	0-30*
	hvdrotreated	3	
Not Available	Polyolefin	Not Available	0-9*
Not Available	Polyolefin amide alkeneamine	Not Available	1-3
Not Available	Mineral oil	Not Available	0-35*
68649-42-3	Phosphorodithioic acid, 0,0-di-C1-		
	14-alkyl esters, zinc salts	acid, zinc salt	
Not Available	Calcium sulfonate	Not Available	0.5-2*
Not Available	Alkylated phenol	Not Available	0.5-3*
Not Available	Alkylamine	Not Available	0.5-2*

٦

Г

Not AvailableAlkylamineNot Available0.5-2*Component Related Regulatory InformationThis product may be regulated, have exposure limits or other information identified as the following: Oil mist, mineral (8012-95-1), Zinc compounds.

* Even though the concentration range does not fall under the ranges prescribed by WHMIS, this is the actual range which varies with each batch of the product.

SECTION 4: FIRST AID MEASURES

INHALATION (BREATHING):	Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Oxygen should only be administered by qualified personnel. Someone should stay with victim. Get medical attention if breathing difficulty persists.
EYES:	If irritation or redness from exposure to vapor develops, move away from exposure into fresh air. Upon contact, immediately flush eyes with plenty of lukewarm water, holding eyelids apart, for 15 minutes. Get medical attention.
SKIN:	Remove affected clothing and shoes. Wash skin thoroughly with soap and water. Get medical attention if irritation or pain develops or persists. If product is injected under pressure into or under the skin, or into any part of the body, regardless of the appearance of the wound or its size, a physician should immediately evaluate the individual as a medical emergency.
INGESTION (SWALLOWING):	Do NOT induce vomiting. Immediately get medical attention. Call 1-888-668-6463 for additional information. If spontaneous vomiting occurs, keep head below hips to avoid breathing the product into the lungs. Never give anything by mouth to an unconscious person.

NOTE TOTreat symptomatically and supportively. Treatment may vary with condition of victim andPHYSICIANS:specifics of incident.

SECTION 5: FIRE FIGHTING MEASURES

HAZARDOUS COMBUSTION PRODUCTS:

Decomposition and combustion materials may be toxic. Burning may produce aldehydes, hydrogen sulfide, alkyl mercaptans, sulfides, carbon monoxide, and oxides of sulfur, calcium and zinc and other unidentified organic compounds.

CONDITIONS OF FLAMMABILITY: Sp

PROTECTIVE EQUIPMENT FOR FIREFIGHTERS:


EXTINGUISHING MEDIA:

NFPA 704 HAZARD IDENTIFICATION: Sparks, or flame. Product may burn, but does not ignite readily.

A positive-pressure, self-contained breathing apparatus (SCBA) and fullbody protective equipment are required for fire emergencies.

Carbon dioxide, regular foam, dry chemical, water spray, or water fog. Water or foam may cause frothing.

This information is intended solely for the use by individuals trained in this system.



FIRE FIGHTING INSTRUCTIONS:

Keep storage containers cool with water spray.

FIRE AND EXPLOSION HAZARDS:

Heated containers may rupture. "Empty" containers may retain residue and can be dangerous. Products are not sensitive to mechanical impact or static discharge.

SECTION 6: ACCIDENTAL RELEASE MEASURES

Remove all ignition sources. Do not touch or walk through spilled product. Stop leak if you can do it without risk. Wear protective equipment and provide engineering controls as specified in **SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION**. Isolate hazard area. Keep unnecessary and unprotected personnel from entering. Ventilate area and avoid breathing vapor or mist. Contain spill away from surface water and sewers. Contain spill as a liquid for possible recovery, or absorb with compatible sorbent material and shovel with a clean, sparkproof tool into a sealable container for disposal.

Additionally, for large spills: Dike far ahead of liquid spill for collection and later disposal.

Revision 03/15; MSDS - Page 4 of 12

SECTION 7: HANDLING AND STORAGE

HANDLING: Keep away from sparks or flame. Where flammable mixtures may be present, equipment safe for such locations should be used. Use clean tools. When transferring large volumes of product, metal containers, including trucks and tank cars, should be grounded and bonded. These products have a low vapor pressure and are not expected to present an inhalation hazard under normal temperatures and pressures. However, when aerosolizing, misting, or heating these products, do not breathe vapor or mist. Use in a well ventilated area. Avoid contact with eyes, skin, clothing, and shoes.

SHIPPING AND
STORING:Keep container tightly closed when not in use and during transport. Store containers in a
cool, dry place. Do not pressurize, cut, weld, braze, solder, drill, or grind containers. Keep
containers away from flame, sparks, static electricity, or other sources of ignition. Empty
product containers may retain product residue and can be dangerous.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

EXPOSURE GUIDELINES:

Component Exposure Limits

Lubricating oils, petroleum, hydrotreated spent (64742-58-1)

ACGIH:	5 mg/m3 TWA (sampled by method that does not collect vapor) (related to Oil mist, mineral)
	10 mg/m3 STEL (sampled by method that does not collect vapor) (related to Oil mist, mineral)
OSHA Final:	5 mg/m3 TWA (related to Oil mist, mineral) 5
OSHA Vacated:	mg/m3 TWA (related to Oil mist, mineral) 5
NIOSH:	mg/m3 TWA (related to Oil mist, mineral)
	10 mg/m3 STEL (related to Oil mist, mineral)

Lubricating oils, petroleum, C20-50, hydrotreated neutral oil-based (72623-87-1)

ACGIH:	5 mg/m3 TWA (sampled by method that does not collect vapor) (related to Oil mist, mineral)
	10 mg/m3 STEL (sampled by method that does not collect vapor) (related to Oil mist, mineral)
OSHA Final:	5 mg/m3 TWA (related to Oil mist, mineral)
OSHA Vacated:	5 mg/m3 TWA (related to Oil mist, mineral)
NIOSH:	5 mg/m3 TWA (related to Oil mist, mineral)
	10 mg/m3 STEL (related to Oil mist, mineral)

Petroleum distillates, hydrotreated heavy paraffinic (64742-54-7)

ACGIH:	5 mg/m3 TWA (sampled by method that does not collect vapor) (related to Oil mist, mineral)
	10 mg/m3 STEL (sampled by method that does not collect vapor) (related to Oil mist, mineral)
OSHA Final:	5 mg/m3 TWA (related to Oil mist, mineral)
OSHA Vacated:	5 mg/m3 TWA (related to Oil mist, mineral)
NIOSH:	5 mg/m3 TWA (related to Oil mist, mineral)
	10 mg/m3 STEL (related to Oil mist, mineral)

Residual oils (petroleum), solvent dewaxed (64742-62-7)

ACGIH:	5 mg/m3 TWA (sampled by method that does not collect vapor) (related to Oil mist, mineral)
	10 mg/m3 STEL (sampled by method that does not collect vapor) (related to Oil mist, mineral)
OSHA Final:	5 mg/m3 TWA (related to Oil mist, mineral) 5
OSHA Vacated:	mg/m3 TWA (related to Oil mist, mineral) 5
NIOSH:	mg/m3 TWA (related to Oil mist, mineral)
	10 mg/m3 STEL (related to Oil mist, mineral)

Lubricating oils (petroleum), C>25, hydrotreated bright stock (72623-83-7) 5 mg/m3 TWA (sampled by method that does not collect vapor) (related to Oil mist, mineral) ACGIH: 10 mg/m3 STEL (sampled by method that does not collect vapor) (related to Oil mist, mineral) 5 mg/m3 TWA (related to Oil mist, mineral) OSHA Final: 5 mg/m3 TWA (related to Oil mist, mineral) **OSHA** Vacated: 5 mg/m3 TWA (related to Oil mist, mineral) NIOSH: 10 mg/m3 STEL (related to Oil mist, mineral) Lubricating oils, petroleum, C15-30, hydrotreated neutral oil-based (72623-86-0) ACGIH: 5 mg/m3 TWA (sampled by method that does not collect vapor) (related to Oil mist, mineral) 10 mg/m3 STEL (sampled by method that does not collect vapor) (related to Oil mist, mineral) **OSHA** Final: 5 mg/m3 TWA (related to Oil mist, mineral) **OSHA** Vacated: 5 mg/m3 TWA (related to Oil mist, mineral) NIOSH: 5 mg/m3 TWA (related to Oil mist, mineral) 10 mg/m3 STEL (related to Oil mist, mineral) Residual oils (petroleum), hydrotreated (64742-57-0) 5 mg/m3 TWA (sampled by method that does not collect vapor) (related to Oil mist, mineral) ACGIH: 10 mg/m3 STEL (sampled by method that does not collect vapor) (related to Oil mist, mineral) **OSHA** Final: 5 mg/m3 TWA (related to Oil mist, mineral) **OSHA** Vacated: 5 mg/m3 TWA (related to Oil mist, mineral) NIOSH: 5 mg/m3 TWA (related to Oil mist, mineral) 10 mg/m3 STEL (related to Oil mist, mineral) Mineral oil (Not Available) ACGIH: 5 mg/m3 TWA (sampled by method that does not collect vapor) (related to Oil mist, mineral) 10 mg/m3 STEL (sampled by method that does not collect vapor) (related to Oil mist, mineral) 5 mg/m3 TWA (related to Oil mist, mineral) 5 OSHA Final: mg/m3 TWA (related to Oil mist, mineral) 5 **OSHA** Vacated: mg/m3 TWA (related to Oil mist, mineral) NIOSH: 10 mg/m3 STEL (related to Oil mist, mineral) **ENGINEERING** Provide general ventilation needed to maintain concentration of vapor or mist below applicable exposure limits. Where adequate general ventilation is unavailable, use process **CONTROLS:** enclosures, local exhaust ventilation, or other engineering controls to control airborne levels below applicable exposure limits.

PERSONAL PROTECTIVE EQUIPMENT

RESPIRATORY PROTECTION: Not normally needed. Use NIOSH-certified P- or R- series particulate filter and organic vapor cartridges when concentration of vapor or mist exceeds applicable exposure limits. Protection provided by air purifying respirators is limited. Do not use N-rated respirators. Selection and use of respiratory protective equipment should be in accordance in the USA with OSHA General Industry Standard 29 CFR 1910.134; or in Canada with CSA Standard 294.4.

EYE Where eye contact is likely, wear chemical goggles; contact lens use is not recommended. **PROTECTION:**

SKINWhere skin contact is likely, wear neoprene, nitrile or equivalent protective gloves; use of
natural rubber or equivalent gloves is not recommended.

When products are heated and skin contact is likely, wear heat-insulating, gloves, boots, and other protective clothing. To avoid prolonged or repeated contact where spills and splashes are likely, wear appropriate chemical-resistant faceshield, boots, apron, coveralls, long sleeve shirts, or other protective clothing. Use good personal hygiene. Wash thoroughly with soap and water after handling product PERSONAL and before eating, drinking, or using tobacco products. Clean affected clothing, shoes, and HYGIENE: protective equipment before reuse. Discard leather articles, such as shoes, saturated with these products. OTHER Where spills and splashes are likely, facilities storing or using these products should be equipped with an emergency eyewash and shower, both equipped with clean water, in the PROTECTIVE immediate work area. EQUIPMENT:

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

PHYSICAL STATE, APPEARANCE, AND ODOR:	Liquid, amber, petroleum odor.
ODOR THRESHOLD:	Not available
MOLECULAR WEIGHT:	Not applicable
SPECIFIC GRAVITY:	0.88 (water = 1) (approximately)
DENSITY:	7.3 LB/US gal (880 g/l) (approximately)
VAPOR DENSITY:	Not available
VAPOR PRESSURE:	less than 0.1 mmHg at 68°F (20°C)
BOILING POINT:	475ºF (246ºC) (minimum)
FREEZING/MELTING POINT:	Not available [pour point 0°F (-18°C) (maximum)].
pH:	Not available.
EVAPORATION RATE:	Not available
SOLUBILITY IN WATER:	Insoluble
FLASH POINT:	383ºF (195ºC) (minimum) Cleveland Open Cup
FLAMMABLE LIMITS IN AIR:	LOWER: Not available UPPER: Not available
AUTOIGNITION TEMPERATURE:	Not available

SECTION 10: STABILITY AND REACTIVITY

STABILITY:	Stable under normal temperatures and pressures.	
CONDITIONS TO AVOID:	Avoid sparks or flame when not in use.	
INCOMPATIBILITY:	Avoid oxidizing agents, acids and reactive halogens.	
REACTIVITY:	Polymerization is not known to occur under normal temperature and pressures. Not reactive with water.	
HAZARDOUS DECOMPOSITION	None under normal temperatures and pressures. See also SECTION 5: HAZARDOUS COMBUSTION PRODUCTS	
PRODUCTS:		
SECTION 11: TOXICOLOGICAL INFORMATION		

TOXICITY DATA:

Component Analysis - LD50/LC50 Lubricating oils, petroleum, hydrotreated spent (64742-58-1) Oral LD50 Rat >2000 mg/kg Dermal LD50 Rat >2000 mg/kg Dermal LD50 Rabbit >4480 mg/kg

Lubricating oils, petroleum, C20-50, hydrotreated neutral oil-based (72623-87-1) Inhalation LC50 Rat 2.18 mg/L 4 h Oral LD50 Rat >5000 mg/kg Dermal LD50 Rabbit >2000 mg/kg

Petroleum distillates, hydrotreated heavy paraffinic (64742-54-7) Inhalation LC50 Rat 2.18 mg/L 4 h Oral LD50 Rat >2000 mg/kg Dermal LD50 Rabbit >2000 mg/kg

Residual oils (petroleum), solvent dewaxed (64742-62-7) Inhalation LC50 Rat 2.18 mg/L 4 h Oral LD50 Rat >5000 mg/kg Dermal LD50 Rabbit >2000 mg/kg

Lubricating oils (petroleum), C>25, hydrotreated bright stock (72623-83-7) Oral LD50 Rat >5000 mg/kg

Lubricating oils, petroleum, C15-30, hydrotreated neutral oil-based (72623-86-0) Inhalation LC50 Rat 2.18 mg/L 4 h Oral LD50 Rat >5000 mg/kg Dermal LD50 Rabbit >2000 mg/kg

Residual oils (petroleum), hydrotreated (64742-57-0) Oral LD50 Mouse 22 g/kg (related to Oil mist, mineral)

Mineral oil (Not Available)

Oral LD50 Mouse 22 g/kg (related to Oil mist, mineral)

ACUTE EFFECTS:	These products are not likely to present an inhalation hazard at normal temperatures and pressures. However, when aerosolizing, misting, or heating these products, high concentrations of generated vapor or mist may irritate the respiratory tract (nose, throat, and lungs). May cause eye and skin irritation. Not likely to be absorbed through the skin in harmful amounts. May be harmful if swallowed. May cause throat irritation, nausea, vomiting, and diarrhea.
REPEATED DOSE EFFECTS:	Prolonged or repeated inhalation of oil mist may cause oil pneumonia, lung tissue inflammation, and/or fibrous tissue formation. Prolonged or repeated eye contact may cause inflammation of the membrane lining the eyelids and covering the eyeball (conjunctivitis). Prolonged or repeated skin contact may cause drying, cracking, redness, itching, and/or swelling (dermatitis). Experimental evidence suggests that these products do not cause mutagenesis. Based on best current information, there is no known sensitization, reproductive toxicity, or teratogenicity associated with these products.
CARCINOGENICITY:	Based on best current information, there is no known carcinogenicity as categorized by ACGIH A1 or A2 substances; as categorized by IARC Group 1, Group 2A, or Group 2B agents; or as listed by NTP as either known carcinogens or substances for which there is limited evidence of carcinogenicity in humans or sufficient evidence of carcinogenicity in experimental animals. Also see SECTION 15: CALIFORNIA .
TARGET ORGAN EFFECTS:	Prolonged or repeated inhalation of oil mist may cause oil pneumonia, lung tissue inflammation, and/or fibrous tissue formation.

SECTION 12: ECOLOGICAL INFORMATION

ECOTOXICITY:	No information available for the product. Component Analysis - Ecotoxicity - Aquatic Toxicity		
	Lubricating oils, petroleum, hydroti Test & Species 96 Hr LC50 Brachydanio rerio 96 Hr LC50 Pimephales promelas	reated spent (647 Results 79.6 mg/L 3.2 mg/L	42-58-1) Conditions semi-static semi-static
	Lubricating oils, petroleum, C20-50, hydrotreated neutral oil-based (72623-87-1)		
	Test & Species 96 Hr LC50 Oncorhynchus mykiss	Results >5000 mg/L	Conditions
	Petroleum distillates, hydrotreated heavy Test & Species96 Hr LC50 Oncorhynchus mykiss>500Residual oils (petroleum), solvent dewaxe Test & Species96 Hr LC50 Oncorhynchus mykiss>500		(64742-54-7) Conditions
			2-7) Conditions
	Lubricating oils (petroleum), C>25, Test & Species 96 Hr LC50 Lepomis macrochirus	hydrotreated brig Results >10000 mg/L	ht stock (72623-83-7) Conditions
	Lubricating oils, petroleum, C15-30, hydrotreated neutral oil-based (72623-86-0)		
	Test & Species 96 Hr LC50 Oncorhynchus mykiss	Results >5000 mg/L	Conditions
	Phosphorodithioic acid, O,O-di-C1- Test & Species 96 Hr LC50 Pimephales promelas 96 Hr LC50 Pimephales promelas	14-alkyl esters, zi Results 1.0-5.0 mg/L 10.0-35.0 mg/L	Conditions static

PERSISTENCE/ DEGRADABILITY:	No information available.
BIOACCUMULATION/ ACCUMULATION:	No information available.
MOBILITY IN ENVIRONMENTAL MEDIA:	No information available.

OTHER ADVERSE EFFECTS: Not available.

OCTANOL/WATER Not available PARTITION COEFFICIENT:

VOLATILE ORGANIC COMPOUNDS: Negligible.

SECTION 13: DISPOSAL CONSIDERATIONS

- **DISPOSAL:** Dispose in accordance with federal, state, provincial, and local regulations. Regulations may also apply to empty containers. The responsibility for proper waste disposal lies with the owner of the waste.
- USEPA WASTE CODE(S): These products, if discarded, are not expected to be a characteristic or listed hazardous waste. If recycled in the USA, they must be managed in accordance with 40 CFR Part 279. Processing, use, or contamination by the user may change the waste code(s) applicable to the disposal of these products.

SECTION 14: TRANSPORT INFORMATION

International Regulations

IATA-DGR Not regulated as a dangerous good IMDG-Code Not regulated as a dangerous good Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code Not applicable for product as supplied. National Regulations

TDG

Not regulated as a dangerous good

SECTION 15: REGULATORY INFORMATION

USA REGULATIONS

OSHA	OSHA Regulated Chemicals No information is available.
SARA SECTIONS 302 AND 304:	Based on the ingredient listed in SECTION 3 , this product does not contain any "extremely hazardous substances" listed pursuant to Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA) Section 302 or Section 304 as identified in 40 CFR Part 355, Appendix A and B.
SARA SECTIONS 311 AND 312:	These products pose the following health hazard(s) as defined in 40 CFR Part 370 and are subject to the requirements of sections 311 and 312 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA): Immediate (Acute) Health Hazard Delayed (Chronic) Health Hazard

SARA SECTION 313:	These products contain "toxic" chemical(s) subject to the requirements of section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA) and 40 CFR Part 372.	
	Phosphorodithioic acid, O,O-di-C1-14-alkyl esters, zinc salts (68649-42-3) % de minimis concentration (Chemical Category N982) (related to Zinc compounds)	
CERCLA:	Based on the ingredient(s) listed in SECTION 3, this product does not contain any "hazardous substances" listed pursuant to the Comprehensive Environmental Response, Compensation and Liability Act of 1980 (CERCLA) in 40 CFR Part 302, Table 302.4.	
TSCA:	All the components of this product are listed on, or are exempted from the requirement to be listed on, the TSCA Inventory.	
CALIFORNIA:	These products may contain a detectable amount of benzene CAS 71-43-2 from additives. These products may contain a detectable amount of benzo(a)anthracene CAS 56-55-3, benzo(b)fluoranthene CAS 205-99-2, benzo(k)fluoranthene CAS 207-08-9, benzo(a)pyrene CAS 50-32-8, chrysene CAS 218-01-9, dibenz(a,h)anthracene CAS 53-70-3 and indeno(1,2,3-cd)pyrene CAS 193-39-5. WARNING: These chemicals are known to the State of California to cause cancer. Our testing of these products indicates that these chemicals are not always detectable.	
	These products may contain a detectable amount of benzene CAS 71-43-2 from	

These products may contain a detectable amount of benzene CAS 71-43-2 from additives. WARNING: This chemical is known to the State of California to cause birth defects or other reproductive harm.

CANADIAN REGULATIONS

These products have been classified in accordance with the hazard criteria of the Controlled Products Regulations (CPR) and the MSDS contains all information required by the CPR.

CANADIAN	The components of this product are listed on, or are exempted from the requirements to
ENVIRONMENTAL	be listed on, the Canadian Domestic Substances List (DSL).
PROTECTION ACT	
(CEPA):	

SECTION 16. OTHER INFORMATION

REVISION INFORMATION:	This MSDS has been revised in the following sections:
	Regulatory update. Revised format (Sections 2 and 3 switched). Section
	1 (Dates/Address), Section 5 (Fire fields), Section 8 (Exposure limits),
	Section 10 (Conditions to Avoid Field), Section 11 (Toxicology fields),
	Section 12 (Component Ecotoxicity), Section 16 (Revision).
LABEL/OTHER INFORMATION:	Not available

User assumes all risks incident to the use of this (these) product(s). To the best of our knowledge, the information contained herein is accurate. However, MOTOSEL assumes no liability whatsoever for the accuracy or completeness of the information contained herein. <u>No</u> representations or warranties, either express or implied, or merchantability, fitness for a particular purpose or of any other nature are made hereunder with respect to information or the product to which information refers. The data contained on this sheet apply to the product(s) as supplied to the user.